

70x100mm, 正反面 105克铜版纸



Nakamichi®
www.nakamichicaraudio.com

NC-3L
Color CMD Camera

SPECIFICATIONS

NC-3L

Image Sensor	Color CMD (Photosensitive Chip)
Lens Angle	90 degrees
TV System	NTSC/PAL
Effective Pixels	510(H)x 492(V)
Horizontal Resolution	420 TVL
Sensing Area	4.08mm X3.102mm
Shutter Speed	1/60-20 μ s
Video Output	RCA Connector; 1.0Vp-p,75 Ω
Power Supply	12V
Operating Temperature	-20 $^{\circ}$ C~+60 $^{\circ}$ C RH 95% Max
Storage Temperature	-20 $^{\circ}$ C~+80 $^{\circ}$ C RH 95% Max
waterproof	IP68
Minimum Illumination	0.1-0.5 Lux/F=1.2 (0 Lux with IR on)

正面

INSTALLATION

Please read these instructions carefully before installation and use. Installation should be performed by professional staff.

1. Wire Connection

Connect the 12V power to the red jack using the Included 1m cable. Use the included 5m cable to connect the yellow RCA to your video monitor.

Attention: The camera switch is controlled by the reverse Gear shift.

2. Installation Method

The camera can be installation the following way:

- External installation (Fig.1)
- Bracket-mount: Install in the rear bumper or on the License plate. Fix the camera with screws.




Fig.1

WHAT'S IN THE BOX

CMD Camera (x1pc) Instruction Manual (x1pc)
1m Power Cable (x1pc) 5m Video Cable (x1pc)
Screws/Nuts (for bracket mount) (x2pcs)

背面